



# CN-4

## Basic line

The CN-4 pneumatic machine is simple, robust and easy to use.

- Good projection capacity of polyurethane.
- Pump direction change system with pneumatic limit switches.
- Double vertical product pump.
- Protective casings for added security.
- ISO automatic lubrication system by slave pump.
- It can work without transfer pumps in an emergency.
- Easy transport.
- You only need compressed air.
- Own design and manufacturing.



**SOLIDWORKS**



Security  
protections



Made in  
Spain

Model	CN-4
Production	8,5 L/min, polyurethane
Work pressure	1450 psi (100 bar)
Electrical power supply	NO
Maximum hose length	282 ft (86 m)
Heaters	NO
Weight	99.2 lb (45 Kg)
Dimensions (width x depth x height)	1.9 x 1.7 x 3.1 ft (590 x 510 x 925 mm)
Electric motor	NO
Transformer	NO



## Characteristics

CE certificate.

Pressure gauges at the outlet of each product.

The reversing system of the pump is initiated by pneumatic switches to prevent piston slams and have a long service life.

All components are easily replaceable and are in stock.

The machine works with vertical piston pumps with ball valves.

The design with easily removable safety guards prevents accidents and allows for easy maintenance.

ISO automatic lubrication system by servo pump.

•Consult for other configurations.

### Optional equipments

Spray gun  
Transfer pumps  
Compressors

Spray gun accessories  
Hoses  
Air dryers

Heating drum bands